The Biggest Thing in Little PC Capable LCD Monitors

LCD-840V LCD-840VL



LCD-840D Rack Mount Unit





LCD-840VL Flush Mount Unit

Active Matrix 8.4" LCD Monitors with PC Capability

- · Wireless remote control
- · Composite, S-Video, and PC capability
- For color and B/W applications
- · Active matrix technology allows wide viewing angle
- · Acitve matrix technology eliminates distortion
- A/C adaptor included
- Response Time: 20ms/30ms (rising/falling)
- Built-in interface for wall or arm mounting VESA 75mm FPMPMI compliant

LCD-840VL 8.4" Unit in Flush Mount Kit

Dimensions (WHD): $290 \times 213 \times 40.6$ mm / 11.4" x 8.4" x 1.6" Installer's Cut-out (WH): 229×175 mm / 9" x 6.9"

Weight: Net: Est. 1.8 kg. / 4 lbs. Gross: Est. 2.7 kg. / 6 lbs.

Optional Accessories

MB-3 Desk stand (shown above) HM-400 Under-cabinet hinge mount

Touchscreen: For 8.4" order LCD-840TS

Display: 8.4" TFT LCD active matrix

Input Signal: NTSC/PAL(auto sensing), S-Video, Analog RGB

Resolution: 800(H) x 600(V) dots Brightness rating: 150 cd/m²(Nit)

Contrast Ratio: 200:1LCD-840 series: 45/45/35/15

Viewing angle L/R/T/B: 55/55/35/15

Power Requirements: Regulated 12 VDC, 3A (LCD-641V: Regulated 12 VDC, 2A)

Power Consumption: 30 W (max)

Video Input Level: 1.0 V P-P (positive) 75 Ohm

Dimensions (WHD): LCD-840D: 19" x 7" (Occupies 4 RU) x 1.75"

LCD-840V: 264 x 163 x 38mm / 10.4" x 6.4" x 1.5"

Actual visible screen size (WH): $\,$ 174 x 131mm / 6.9" x 5.2"

Operating temperature: $50 \sim 104$ °F or $10 \sim 40$ °C Connections: RCA video IN. S-Video.

BNC video IN, S-video,

2.1 DC IN jacks,

15-pin mini D-sub (female)

Weight: LCD-840D: Net: 2.5 kg. / 5.6 lbs. Gross: 5.4 kg. / 12 lbs.

LCD-840V: Net: 3.2 kg. / 5.4 lbs. Gross: 3.6 kg. / 8 lbs.

LCD-840VL: Net: Est. 2.9 kg. / 6.4 lbs. Gross: 4.1 kg. / 9 lbs.

Specifications subject to change without notice

©2008 ToteVision

30K

Available through:

• Seattle, WA 98109 :: 206-623-6609 ision.com